




Car washing Next Generation

Q/block Qblock



Basic configuration

- Hot Dipped Galvanized Frame, Painted and Oven Finished
- Two Motor Gantry Drive
- Three Chemical Pumps for Detergent, Wax and Foam Bath
- Top Washer and Drying Unit Electric Lifting Devices - Variable speed
- Electric Traveling Side Washers
- Overlapping Front & Rear Side Washers
- Foam Bath
- Amp Sensing for Top and Side Washers
- THREE Carlite® Brushes
- Tow Hook Safety Kit
- Stainless Steel Top Contouring Dryer, Three Position Pivoting Vent (2 x 3 kW motors)
- Two Side Dryers (2 x 4kW)
- PLC with up to 15 wash programs
- Programmer with Message Display and Wash Counter
- Variable Frequency Drive
- 9 m Hot Dipped Galvanized Track
- Manual Activation by keypad
- Stainless Steel Bolts and Nuts
- ABS front doors with traffic lights
- Standard Supply: 380 / 415 V - 50 Hz
- FIA29 Qblock patented system, including Frost Protection, Doors and Magnets (for vehicles detection in the washing area)
- Rails gauge : m 3,28
- Washing width: m 2,50
- Wash & Dry Heights available:
2.25 m or 2.55 m

Accessories

- Filament, Ultralight or Textile Top & Side Brushes
- Rim washer with chemical pump
- Mosquito/Bug Remover
- Foaming Polish Wax with pre dryer
- Underchassis Wash Systems
- Self-serve activation systems
- Automatic Frost Protection Devices
- Floor wash Device
- Remote diagnostic devices
- Wheel washer Devices (Brushes / Rotating Heads)
- Various high pressure devices